



Model XJ-A235U 2000 Lumens





Never Change a Mercury Lamp Again! You Could Save Up to \$800.*

You could save up to \$800. based on a comparison to prior Casio product with a mercury Lamp.

At only 1.7 inches thick it is the thinnest high brightness projector in the industry.+



WIDESCREEN

Get the whole picture with widescreen!








2X OPTICAL ZOOM

The 2X Optical Power Zoom makes it easier to fit your presentation on the screen.



нрм

Direct Digital Input



provide the thumb driv provide the software to convert: PowerPoint®, Microsoft Word®,Microsoft Excel® and Adobe® PDF's.





WIRELESS LAN AVAILABLE (802.11b/g/n)


Wirelessly connect up to 4 laptops with the projector. Wireless LAN is optional and sold separately.



CONSISTENT BRIGHTNESS & COLOR

The new hybrid light source loses less than 3% in 2,000 hours. Casio mercury lamps lose 50% of brightness in 2,000 hours.





SUPER COLOR

Hybrid light source results in a 50% increase in the color spectrum. This results in richer color.*



PICTURE BY DLP



VALUE AND A GREAT WARRANTY

Estimated Light Source Life is 20,000 hours. 3 years Casio warranty*





GREEN SLIM
PROJECTOR



visit: www.greenslimprojector.com



BASIC SPECIFICATIONS		
Brightness		2000 lumens
Contrast ratio		1800 : 1
Projection lens		2X Power zoom & focus
Lens offset		
		84%
Light Source		Laser & LED hybrid technology
Estimated Operating Life	1	up to 20,000 hours (waranty 3 years or 6,000 hours)
Projection screen size		18 ~ 300-inch
Projection range	60-inch screen	4.62 ft ~ 9.24 ft
	100-inch screen	7.92 ft ~ 15.84 ft
	Minimum	2.77 ft
	Projection ratio	1.15 - 2.30:1
Projection system		DLP® system
Display element	Device Type	0.65-inch DLP® chip
	Native Resolution	WXGA (1200 x 800) 1,024,000 pixels
	Native Aspect Ratio	16:10
Color reproduction	ranve repositions	Full color (16.77 million colors)
Power source		,
	Auto	AC100~240V, 50/60Hz
Keystone correction		+30° Vertical
Dimensions	Manual	±30° Vertical
Dimensions		11.69" x 8.26" x 1.69" incl. projections
NA7. 1. 1.		1.58" (at thinnest point excl. projections)
Weight		5.0 lbs
Ceiling mount		Yes (mount available separately from 3rd party vendors)
Power consumption	Operating	270W (Eco Off) / 190W Eco On Level 1) / 130W (Eco On Level 2)
	Standby	100 - 120V (0.4W), 220 - 240V (0.6W)
Security compatibility	Kensington compatible	Yes
	Power ON password	Yes
INTERFACE TERMINALS		
RGB/Component		mini D-Sub 15 pin x 1
Video Input		Also use as YcbCr/YPbPr input
Native Resolution		WXGA (1280 x 800) 1,024,000 pixels
Computer Signal Compatibility (max.)		UXGA (1600 x 1200) (Compressed)
Computer Signal Compatibility (max.) Resolutions		UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA,
Resolutions		UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA
Resolutions Digital input		UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P)
Resolutions	Input	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack
Resolutions Digital input	Input Output	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker
Resolutions Digital input Audio	<u> </u>	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input)
Resolutions Digital input	<u> </u>	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack
Resolutions Digital input Audio Video	Output Input terminals	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr
Resolutions Digital input Audio	Output	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/
Resolutions Digital input Audio Video Video Signal	Output Input terminals Video Systems	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM
Resolutions Digital input Audio Video Video Signal Compatibility	Output Input terminals Video Systems DTV/HDTV	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p
Resolutions Digital input Audio Video Video Signal	Output Input terminals Video Systems	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5)
Resolutions Digital input Audio Video Video Signal Compatibility Control	Output Input terminals Video Systems DTV/HDTV	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability	Output Input terminals Video Systems DTV/HDTV	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately
Resolutions Digital input Audio Video Video Signal Compatibility Control	Output Input terminals Video Systems DTV/HDTV Terminal	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability	Output Input terminals Video Systems DTV/HDTV Terminal Connectable	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included)
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability	Output Input terminals Video Systems DTV/HDTV Terminal	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability	Output Input terminals Video Systems DTV/HDTV Terminal Connectable	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included)
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability	Output Input terminals Video Systems DTV/HDTV Terminal Connectable	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included) USB memory (commercially available) (Not Included) CASIO's Digital Camera/Graphic calculator/Electronic dictionary (Not Included)
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability USB	Output Input terminals Video Systems DTV/HDTV Terminal Connectable	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included) USB memory (commercially available) (Not Included) CASIO's Digital Camera/Graphic calculator/Electronic dictionary (Not Included)
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability USB	Output Input terminals Video Systems DTV/HDTV Terminal Connectable Equipment	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included) USB memory (commercially available) (Not Included) CASIO's Digital Camera/Graphic calculator/Electronic dictionary (Not Included) 41~95°F 20~80% (non-condensation)
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability USB OTHERS Usage environment	Output Input terminals Video Systems DTV/HDTV Terminal Connectable Equipment Operating temperature	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included) USB memory (commercially available) (Not Included) CASIO's Digital Camera/Graphic calculator/Electronic dictionary (Not Included) 41~95°F 20~80% (non-condensation) Yes (for operation 3,300~6,600 ft)
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability USB OTHERS Usage environment Remote controller range	Output Input terminals Video Systems DTV/HDTV Terminal Connectable Equipment Operating temperature Operating humidity	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included) USB memory (commercially available) (Not Included) CASIO's Digital Camera/Graphic calculator/Electronic dictionary (Not Included) 41~95°F 20~80% (non-condensation) Yes (for operation 3,300~6,600 ft) 16.5 ft maximum
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability USB OTHERS Usage environment	Output Input terminals Video Systems DTV/HDTV Terminal Connectable Equipment Operating temperature Operating humidity	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P ? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included) USB memory (commercially available) (Not Included) CASIO's Digital Camera/Graphic calculator/Electronic dictionary (Not Included) 41~95°F 20~80% (non-condensation) Yes (for operation 3,300~6,600 ft) 16.5 ft maximum 3 years Parts and Labor plus 3 years or 6,000 hour light source
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability USB OTHERS Usage environment Remote controller range Limited Warranty	Output Input terminals Video Systems DTV/HDTV Terminal Connectable Equipment Operating temperature Operating humidity	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P ? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included) USB memory (commercially available) (Not Included) CASIO's Digital Camera/Graphic calculator/Electronic dictionary (Not Included) 41~95°F 20~80% (non-condensation) Yes (for operation 3,300~6,600 ft) 16.5 ft maximum 3 years Parts and Labor plus 3 years or 6,000 hour light source (see Warranty Statement included with product for complete details)
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability USB OTHERS Usage environment Remote controller range	Output Input terminals Video Systems DTV/HDTV Terminal Connectable Equipment Operating temperature Operating humidity	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included) USB memory (commercially available) (Not Included) USB memory (commercially available) (Not Included) 41~95°F 20~80% (non-condensation) Yes (for operation 3,300~6,600 ft) 16.5 ft maximum 3 years Parts and Labor plus 3 years or 6,000 hour light source (see Warranty Statement included with product for complete details) Wireless remote control, RGB cable, AV cable, AC Power Cord,
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability USB OTHERS Usage environment Remote controller range Limited Warranty Included Accessories	Output Input terminals Video Systems DTV/HDTV Terminal Connectable Equipment Operating temperature Operating humidity	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P ? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included) USB memory (commercially available) (Not Included) CASIO's Digital Camera/Graphic calculator/Electronic dictionary (Not Included) 41~95°F 20~80% (non-condensation) Yes (for operation 3,300~6,600 ft) 16.5 ft maximum 3 years Parts and Labor plus 3 years or 6,000 hour light source (see Warranty Statement included with product for complete details) Wireless remote control, RGB cable, AV cable, AC Power Cord, Projector & Accessory Soft Case, Manual on CD-ROM & booklet
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability USB OTHERS Usage environment Remote controller range Limited Warranty	Output Input terminals Video Systems DTV/HDTV Terminal Connectable Equipment Operating temperature Operating humidity	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P ? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included) USB memory (commercially available) (Not Included) CASIO's Digital Camera/Graphic calculator/Electronic dictionary (Not Included) 41~95°F 20~80% (non-condensation) Yes (for operation 3,300~6,600 ft) 16.5 ft maximum 3 years Parts and Labor plus 3 years or 6,000 hour light source (see Warranty Statement included with product for complete details) Wireless remote control, RGB cable, AV cable, AC Power Cord, Projector & Accessory Soft Case, Manual on CD-ROM & booklet YW-3 (Wireless 802.11b/g/n adapter) YK-5 (RS-232C adapter)
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability USB OTHERS Usage environment Remote controller range Limited Warranty Included Accessories Optional Accessories	Output Input terminals Video Systems DTV/HDTV Terminal Connectable Equipment Operating temperature Operating humidity	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P ? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included) USB memory (commercially available) (Not Included) CASIO's Digital Camera/Graphic calculator/Electronic dictionary (Not Included) 41~95°F 20~80% (non-condensation) Yes (for operation 3,300~6,600 ft) 16.5 ft maximum 3 years Parts and Labor plus 3 years or 6,000 hour light source (see Warranty Statement included with product for complete details) Wireless remote control, RGB cable, AV cable, AC Power Cord, Projector & Accessory Soft Case, Manual on CD-ROM & booklet YW-3 (Wireless 802.11b/g/n adapter) YK-5 (RS-232C adapter) YK-CASE01 (Soft Carry Case with handle and shoulder strap)
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability USB OTHERS Usage environment Remote controller range Limited Warranty Included Accessories Optional Accessories Included Software	Output Input terminals Video Systems DTV/HDTV Terminal Connectable Equipment Operating temperature Operating humidity	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P ? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included) USB memory (commercially available) (Not Included) CASIO's Digital Camera/Graphic calculator/Electronic dictionary (Not Included) 41~95°F 20~80% (non-condensation) Yes (for operation 3,300~6,600 ft) 16.5 ft maximum 3 years Parts and Labor plus 3 years or 6,000 hour light source (see Warranty Statement included with product for complete details) Wireless remote control, RGB cable, AV cable, AC Power Cord, Projector & Accessory Soft Case, Manual on CD-ROM & booklet YW-3 (Wireless 802.11b/g/n adapter) YK-5 (RS-232C adapter) YK-CASE01 (Soft Carry Case with handle and shoulder strap) Wireless Connection 3/EZ-Converter FA/ArcSoft Media Converter 3
Resolutions Digital input Audio Video Video Signal Compatibility Control Wireless capability USB OTHERS Usage environment Remote controller range Limited Warranty Included Accessories Optional Accessories	Output Input terminals Video Systems DTV/HDTV Terminal Connectable Equipment Operating temperature Operating humidity	UXGA (1600 x 1200) (Compressed) SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA HDMI x 1 (480P ? 1080P) 3.5mm mini-jack 1 W speaker 3.5mm mini-jack (shared with Audio Input) Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr NTSC/PAL/PAL-N/PAL-M/ PAL60/SECAM 480i/480P/576i/576P/720P/1080i/1080p RS-232C adapter cable (YK-5) required and sold separately Optional (YW-3) 802.11 b/g/n adapter required and sold separately Type A x 1, USB (2.0) Host Multi-functional camera system YC-400/430 (Not Included) USB memory (commercially available) (Not Included) CASIO's Digital Camera/Graphic calculator/Electronic dictionary (Not Included) 41~95°F 20~80% (non-condensation) Yes (for operation 3,300~6,600 ft) 16.5 ft maximum 3 years Parts and Labor plus 3 years or 6,000 hour light source (see Warranty Statement included with product for complete details) Wireless remote control, RGB cable, AV cable, AC Power Cord, Projector & Accessory Soft Case, Manual on CD-ROM & booklet YW-3 (Wireless 802.11b/g/n adapter) YK-5 (RS-232C adapter) YK-CASE01 (Soft Carry Case with handle and shoulder strap)

